

Stationary All-Electric

Dealer Hot Water Pressure Washers



DHA Series — Belt Drive



The DHA Series is all-electric and features a patented heat exchanger design to provide consistent and efficient hot water on-demand.

PUMP

- · Forged brass manifold
- · Stainless-steel and brass unloader valve
- · Forged brass manifold
- Thermal relief valve

MOTOR

- Open drip-proof electric motor with manual thermal overload protection
- On/off power switch

FRAME

· Stainless-steel base and frame with rubber isolators

COMPONENT

Time delay shutdown

HEAT EXCHANGER

- Patented cartridge design
- · Used for consistent and efficient on-demand hot water
- 120°F to 130°F temperature rise above in-take water, obtained within 3 to 5 minutes

- · Adjustable thermostat
- On/Off power switch
- Powder coated steel frame
- Low maintenance, stainless-steel coils in aluminum casings for maximum efficiency
- Eliminates constant cleaning and heat loss

UNIT INCLUDES

- Quick connect nozzles 0°, 15°, 25° and 40°
- External downstream detergent injector with detergent nozzle
- 50-foot x $\%\mbox{-inch-inch}$ steel wire-braided high pressure black hose
- Adjustable pressure insulated dual lance with trigger gun

LIMITED WARRANTIES

1 year electric motor

CERTIFICATION

ETL certified - US and Canada



Stationary All-Electric Hot Water – DHA Series – Belt Drive

MODEL NUMBER	PSI	GPM	HORSEPOWER/ MOTOR	UNIT AMPERAGE	PUMP	HEATER kW	TEMPERATURE RISE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
DH-2503-AE0E4G	2500	2.8	6.0 HP, 480V, 3Ø	68.0A	General	48	120°F	36x25x49in.	725 lb.	625 lb.
DH-3004-AE0E4G	3000	3.9	8.0 HP, 480V, 3Ø	100.0A	General	72	130°F	36x25x49in.	830 lb.	725 lb.

OPTIONS:

P/	ART NUMBER	DESCRIPTION	FITS MODELS
H)	(-0298	Remote box – Adds control box, may be mounted away from unit to control on/off, controls the hot water heater and cold water pump	
H)	(-0307	Auto start/stop – When trigger gun is released, the timer will turn unit off; when trigger gun is pulled, unit will restart	All models



