

#### DHL Series — Belt Drive



DH-1502-LP2E1A (LP tank shown not included)

*This industrial series delivers powerful cleaning power when it is needed the most. It is a self-contained cart-mount unit and easy to move from one jobsite to the next.*

#### PUMP

- Factory preset unloader

#### MOTOR

- Open drip-proof electric motor
- 35-foot power cord with GFCI

#### FRAME

- Reinforced powder coated cabinet-style steel frame
- 10-inch flat-free tires

#### COMPONENTS

- LP gas-fired (vapor only) natural draft with aspirating-type burner
- High limit temperature control for added safety
- LP gas regulator

#### MISCELLANEOUS

- Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F
- Water output temperature is 250°F plus unit operates at 350-PSI in "wet" steam (DH-0703-LP2E1A)

#### UNIT INCLUDES

- Quick connect nozzles – 0°, 15°, 25°, 40° and detergent nozzle
- 50-foot x 3/8-inch steel wire-braided high pressure hose
- 36-inch insulated lance
- Professional-grade insulated trigger gun with safety lock-off

#### LIMITED WARRANTY

- 1 year electric motor

#### CERTIFICATION

- CSA Certified – US and Canada



# Portable LP

## Hot Water – DHL Series – Belt Drive

MODEL NUMBER	PSI	GPM	HORSEPOWER/MOTOR	PUMP	PLUG TYPE	LP GAS BTU PER HOUR	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
DH-0703-LP2E1A*	700	2.3	1.5 HP, 120V, 1Ø, 13.2A	AR	NEMA 5-15P	200,000	57.5x35.5x59.5in.	471 lb.	348 lb.
DH-1502-LP2E1A	1500	1.8	2.0 HP, 120V, 1Ø, 18.8A	AR	NEMA 5-20P	200,000	57.5x35.5x59.5in.	505 lb.	382 lb.

\*Combination wet steam cleaner/pressure washer.



NEMA 5-15P,  
15-amp plug



NEMA 5-20P,  
20-amp plug



DH-1502-LP2E1A

**WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).