

SUNFIRE®

HEATS UP TO 2,800 SQ. FT.


SF120 RADIANT HEATER 120,000 BTUs



LOW NOISE



ODORLESS



ZERO CO
EMISSIONS*



DUST FREE
EXPERIENCE



XTREME CLEAN™
ADVANCED TECHNOLOGY BURNER

DUAL FUEL
DIESEL/#2  KEROSENE

* Requires 120V of electricity.



THERMOSTAT CONTROL OPTION
CONNECT TO STANDARD WALL THERMOSTAT
(THERMOSTAT NOT INCLUDED)

**MADE IN
USA**

* Zero CO with properly tuned burner and at steady state temperature.

THE ULTIMATE HEATING EXPERIENCE



Advanced technology extends nozzle life and improves burn efficiency to achieve zero* carbon monoxide emissions for superior indoor performance and safety.

*Zero CO with properly tuned burner and at steady state temperature.



Hatch under burner cover offers quick access to the nozzle assembly making tune-ups and maintenance ultra-fast and easy.



Multi-Lift Bracket
(Hook/Strap/Forklift)

Safety Tip Switch Included

Wall Thermostat Control Option
(Thermostat not included)

Collapsible Handle

Heavy-Duty Construction

Upward Tilt Capability

Comfort Grip Steel Tube Frame

Quick Change Spin-On Fuel Filter

Flat-Free Rubber Wheels

Easy-Fill Fuel Neck

Available Accessory: Fuel-Filter Heating Band. Improves startup in extreme cold conditions.

Requires proper ventilation indoors. Not for household residential use.

SPECIFICATIONS

BTU/Hr:	120,000	Weight:	120 lbs. Fully Fueled: 218 lbs.	Thermostat Options: Use any mechanical or battery operated wall thermostat. Do not use a thermostat that requires 120V of power. <i>Thermostat not included.</i>
Fuel:	Diesel, #2 Fuel Oil, Kerosene	Product Dimensions:	32"L x 28.5"W x 33.75"H	
Flow Rate GPH:	.87 Diesel and .78 Kerosene	Run Time:	16 Hrs. Diesel / 18 Hrs. Kerosene	
Tank Capacity:	14 Gallons	Minimum Clearances:	Front: 84" Sides: 36" Back: N/A	
Electrical Requirements:	120V 1.2A 60HZ (800W+ Pure Sine INV)	<i>Keep away from combustible items.</i>		

SUNFIRE



SunFireHeaters.com